
## **CUSTOM SIZE SIGN TO BE DETERMINED**





Powder Costed alluminum back-panel:
Face - 175 ( 5052 alloy ) weiged joints
Sides - 3" desp: same materials as face
Powder costing - Steemin Williams usugh testure
polyesiar Super Durable
Swetzural - 3" x 1 4" and 1 1,3" x 1,4" aluminum angle
Mounting - 1,2" steel suits embedded into fearne to accept
1,2" steel suits embedded into fearne to accept Back structural and mounting hardware details

T x 250 aluminum angle weeded sinc the cores of a secure of the planes and 3" tasts panel returns - It also houses 12" mounting nut assembly. 1.5 x. 125 steel flat bar w 1/2" null andja with hyels (or bolts) to accept 1/2" hreaded red that will be used to hang sign on store front Threaded rod nuts spaced every 4 along top and bottom edges Ut, reds - there must be a layer of clear polycerismise under the acylic of of the latter to mak Ut, regulations because of till presence of 120v AC power. 2" x 250 stuminum an 1.2" threaded rod

Install method - through wall Fasteners - 1/2" threaded rod

On typical stud and siding or stud and EFIS wall

- 1/2" threaded rod turned into the nut embedded into the sign's frame 2"x6" pine board ( treated if in a wet area ) along top and bottom of sign to bridge across the wall studs conduit housing 120v wiring to be connected to power source per code

If the wall is solid block or concrete - blocking may not be necessary Electrical Hook Up: Sign requires 10 amp / 120v.

D

150

HOMERS FURNITURE

THE PLACE

GOOD EATS

44